

型号 Item No.	VMC-650	VMC-850	VMC-857	VMC-1060	VMC-1168
工作台 / Worktable					
工作台面积 (mm) Table Size	800x420	1050x500	1000x530	1300x600	1300x650
T型槽 (宽*槽数*间距) T-slot (Width x No. x Distance)	18mmx3pcsx135mm	18mmx5pcsx90mm	18mmx5pcsx100mm	18mmx5pcsx120mm	18mmx5pcsx120mm
最大载重 (kg) Max. Loading Capacity	600	600	600	600	1000
行程 / Travel					
X轴行程 (mm) X-axis Travel	650	800	800	1000	1100
Y轴行程 (mm) Y-axis Travel	400	500	500	600	600
Z轴行程 (mm) Z-axis Travel	480	550	700	600	750
主轴鼻端面至工作台距离 (mm) Distance from spindle nose to table surface	80-560	105-655	110-810	180-780	110-860
主轴中心至立柱导轨距离 (mm) Distance from Spindle center to column guideway	480	550	575	600	690
主轴 / Spindle					
主轴转速 (rpm) Spindle Rotation Speeds	8000R.P.M, (Optical 10000/12000/15000R.P.M)				8000
主轴规格 Spindle Taper	BT40	BT40	BT40	BT40	BT40
主轴马达 (kw) Spindle Motor	5.5	7.5	7.5	11	11
三轴电机功率 (kw) Distance from spindle nose to table surface	1.5	3	3	3	3
进给 / Feed					
X、Y、Z轴快速进给 (mm/min) X、Y、Z axis rapid feedrate	18000	18000	18000	18000	15000
精度 / Accuracy					
定位精度 (mm) Positioning Accuracy	±0.01	±0.01	±0.01	±0.01	±0.01
重复定位精度 (mm) Repeatability	±0.005	±0.005	±0.005	±0.005	±0.005
机床尺寸重量 / Dimension & Weight					
外观尺寸 (mm) Dimensions	2500x2380x2576	2750x2518x2565	2800x2600x2750	3220x2605x3090	3300x2750x3090
机械重量 (kg) Weight	4500	5500	6000	8500	8800

型号 Item No.	VMC-1270	VMC-1370	VMC-1580	VMC-1690	VMC-1890
工作台 / Worktable					
工作台面积 (mm) Table Size	1360x700	1400x710	1700x800	1800x900	2000x900
T型槽 (宽*槽数*间距) T-slot (Width x No. x Distance)	18mmx5pcsx152.5mm	18mmx5pcsx152.5mm	22mmx5pcsx135mm	22mmx5pcsx165mm	22mmx5pcsx165mm
最大载重 (kg) Max. Loading Capacity	1000	1000	1500	1600	1600
行程 / Travel					
X轴行程 (mm) X-axis Travel	1200	1300	1500	1600	1800
Y轴行程 (mm) Y-axis Travel	700	700	800	900	900
Z轴行程 (mm) Z-axis Travel	600	650	700	680	680
主轴鼻端面至工作台距离 (mm) Distance from spindle nose to table surface	150-750	150-800	170-870	160-840	160-840
主轴中心至立柱导轨距离 (mm) Distance from Spindle center to column guideway	785	785	800	950	950
主轴 / Spindle					
主轴转速 (rpm) Spindle Rotation Speeds	8000	8000	8000	8000	8000
主轴规格 Spindle Taper	BT50	BT50	BT50	BT50	BT50
主轴马达 (kw) Spindle Motor	15	15	18.5	18.5	22.5
三轴电机功率 (kw) Distance from spindle nose to table surface	3	3	4.5	4.5	4.5
进给 / Feed					
X.Y.Z轴快速进给 (mm/min) X、Y、Z axis rapid feedrate	12000	12000	12000	12000	12000
精度 / Accuracy					
定位精度 (mm) Positioning Accuracy	±0.01	±0.01	±0.01	±0.01	±0.01
重复定位精度 (mm) Repeatability	±0.005	±0.005	±0.005	±0.005	±0.005
机床尺寸重量 / Dimension & Weight					
外观尺寸 (mm) Dimensions	3600x3100x3150	3800x3195x3230	4255x3605x3380	4350x3750x3380	4500x3805x3380
机械重量 (kg) Weight	9000	10000	12000	13000	14500