

技术参数表			TECHNICAL DATA						YE90W		
规格	Specification		80VE/80V			150VE/150V			200VE/200V		
注射部件	Injection Unit	单位	A	B	C	A	B	C	A	B	C
螺杆直径	Screw diameter	[mm]	20	22	26	26	28	32	28	32	36
长径比	Screw L/D ratio	[L/D]	20	20	18	21	21	19	22	21	18.7
注射容积	Cylinder head volume	[cm³]	28	34	47	58	67	88	77	100	127
注射重量	Shot weight	[g]	25	31	43	53	61	80	70	91	116
注射压力	Injection pressure	[Mpa]	270	223	160	255	220	168	261	200	158
注射速率	Injection rate	[g/s]	57/100	69/121	97/169	97/169	112/196	146/256	112/196	146/256	185/324
注射速度	Shot speed	[mm/s]	200/350			200/350			200/350		
注射行程	Injection stroke	[mm]	90			110			125		
螺杆转速	Screw speed	[rpm]	400			400			400		
喷嘴接触力	Nozzle touch force	[KN]	14.8			14.8			19.7		
喷嘴球径	Sphere diameter of nozzle	[mm]	SR10			SR10			SR10		
合模装置	Clamping Unit										
合模力	Clamping force	[KN]	900								
最大开模行程	Max.mould opening stroke	[mm]	320								
拉杆间距	Space between tie bars	[mm]	420 x 370								
最小模具尺寸	Min.Mould size	[mm]	270 x 240								
最小模厚	Min.Mould height	[mm]	150								
最大模厚	Max.Mould height	[mm]	420								
模厚定位孔直径	Dia of mould location hole	[mm]	Φ100H7								
顶出行程	Ejector stroke	[mm]	80								
顶出力	Ejector force	[KN]	31.4								
顶出杆数	Ejector number	[PIECE]	5								
其他	Others										
电机功率	Motor power	[Kw]	8.9/9.5			11.8/11			14.5/15		
料筒电热功率	Heating power	[Kw]	5.25			7.95			9.25		
加热段	Heating section		3+3			3+3			3+3		
机器尺寸	Machine dimension	[m]	4.56 x 1.34 x 1.63			4.56 x 1.34 x 1.63			4.68 x 1.34 x 1.63		
机器重量	Machine weight	[t]	3.8			4.0			4.2		

注意: *公司具有随时更改型号、参数、规格、配置、颜色的权力, 恕不另行通知。
Attention: * Our company reserves the right of changing model, parameter, specification, configuration and color without prior notice.