

型号	Model	XSM30-16	XSM30-14	XSM30-12	XSM75-16	XSM75-14	XSM75-12	XSM-D-30/30	XSM-D-30/75	XSM75-75	
输出量	Output quantity(kg/hr)	1.1~38	0.6~20	0.3~10	0.5~17	0.2~8	0.1~4	*	*	*	
马达功率	Motor power(w)	60	60	60	60	60	60	60x2	XSM-D-30/75	XSM75-75	
马达转速	Rotation of moto(rpm)	0~3000	0~3000	0~3000	0~3000	0~3000	0~3000	0~3000	XSM-D-30/75	XSM75-75	
储料桶	Material storage tube(L)	10	10	10	10	10	10	10	XSM-D-30/75	XSM75-75	
减速比	Outer diameter of screw bar	30:1	30:1	30:1	75:1	75:1	75:1	30:1/30:1	30:1/75:1	75:1/75:1	
螺杆外径	Reduction ratio(mm)	16	14	12	16	14	12	**	**	**	
主原料斗	Main	选配for selection						标准Standard			
搅拌器	Stirrer	选配for selection						标准Standard			
搅拌器功率	Power of stirrer	0.06KW						0.06KW			
搅拌器电压	Voltage of stirrer	1Φ, 220V, 50HZ						1Φ, 220V, 50HZ			
主电压	Main voltage	1Φ, 220V, 50HZ						1Φ, 220V, 50HZ			
外型 Overall appearance	H(mm)	530						530			
	W(mm)	350						350			
	L(mm)	600						900			
重量	Weight(kg)	21						33			