

型号	冷却水量 (m <sup>3</sup> /h)	风机直径 (mm)	电机功率 (KW)	进塔水压 (kPa)	制品重量 (KG)	运转重量 (KG)	噪音 DB(A)	直径D mm	高H mm
XT-6T	6	400	0.18	19.6	40	90	55	730	1500
XT-8T	8	500	0.18	19.6	50	110	55	950	1550
XT-10T	10	500	0.18	19.6	50	110	55	950	1650
XT-12T	12	550	0.25	19.6	60	130	55	1150	1700
XT-16T	16	600	0.25	19.6	100	310	55	1150	1850
XT-20T	20	700	0.37	24.5	113	327	57	1350	1950
XT-25T	25	700	0.37	24.5	144	447	57	1400	2050
XT-30T	30	730	0.55	27	165	666	57	1540	2200
XT-40T	40	800	0.75	27	250	730	59	1600	2300
XT-50T	50	900	1.1	27	423	753	59	1900	2550
XT-60T	60	1200	1.5	28	521	900	64	2100	2650
XT-70T	70	1200	1.5	28	280	913	64	2100	2650
XT-80T	80	1500	3.0	28	713	1023	64	2350	2750
XT-100T	100	1500	3.0	29	908	1148	65	2900	2850
XT-125T	125	1500	3.0	29	1050	1588	65	2900	2850
XT-135T	135	1800	3.0	29	1160	1720	65	3190	3615
XT-150T	150	2000	4.0	34	1613	3317	65	3780	3805
XT-175T	175	2000	4.0	34	1796	3465	65	3780	3900
XT-200T	200	2800	5.5	35	1810	3514	67	4460	4595
XT-250T	250	2800	5.5	35	1950	3550	69	4460	4610
XT-300T	300	3400	7.5	39	3430	5110	69	5450	4705
XT-350T	350	3400	7.5	39	3800	5480	69	5450	5205