

型号 Model	最高温度 ℃	冷却方式	电热功率 KW	泵浦功率 KW	最大流量 (L/min)	最大压力 Bar	泵浦形式	模具接头 (Inch)	外型尺寸 (mm)	重量kg
XCM-6-W	水式 95℃	直接冷却	6	0.37	30	3.5	卧式	3/8"2x2	850x350x650	62
XCM-9-W			9	0.75	45	3.5		3/8"2x2	850x350x650	90
XCM-12-W			6x2	0.75	45	3.5		3/8"4x2	850x350x650	110
XCM-18-W			6x3	1.5	75	3.5		3/8"4x2	850x400x700	125
XCM-24-W			6x4	3	75x2	5.5		3/8"4x2	900x600x1000	140
XCM-36-W			6x6	3	75x2	5.5		3/8"6x2	900x600x1000	170
XCM-6-O	油式 160℃	间接冷却	6	0.37	30	3.5		3/8"2x2	850x350x650	75
XCM-9-O			9	0.75	45	3.5		3/8"2x2	850x350x650	100
XCM-12-O			6x2	0.75	45	3.5		3/8"4x2	850x350x650	125
XCM-18-O			6x3	1.5	75	3.5		3/8"4x2	850x400x700	145
XCM-24-O			6x4	3	75x2	5.5		3/8"4x2	900x600x1000	185
XCM-36-O			6x6	3	75x2	5.5		3/8"6x2	900x600x1000	200