

规格 Specifications		FY-03AC	FY-05AC	FY-08AC	FY-10AC	FY-12AC	FY-15AC	
4.4/38℃冷量 Cooking capacity(Kacl/h)		6800	12040	19000	25200	34400	37000	
压缩机 Compressor		全封闭涡旋式 All-closed Vorticity						
压缩机输入功率 Compressor power(Kw)		2.5	4.4	7	9	10.2	13.4	
冷媒 Refrigerant		R22(R407,R502环保型选配)						
冻水泵输入功率 Chilled water pump power(Kw)		0.75	0.75	0.75	0.75	1.5	1.5	
10℃冷冻水最大流量 Max flow rate of chilled water(L/min)		55	120	120	200	400	400	
最大扬程 Max pressure(M)		9	9	9	16	20	20	
冻水进出水管 Flow water inlet and outlet pipe(″)		1″	1″	1″	1.5″	1.5″	1.5″	
冷却风机功率 Cooling fan power(Kw)		0.25	0.5	0.5	0.5	0.5	1	
风冷箱式外形	长 Size length(mm)	900	1300	1400	1500	1500	1350	
	宽 Size width(mm)	600	600	750	750	750	1250	
	高 Size height(mm)	1000	1050	1350	1350	1350	1600	
水箱容量 Water tank capa.(L)		40.5	81	117	160	160	234	
重量 Weight(Kg)		210	290	400	450	500	550	

规格 Specifications		FY-20AC	FY-25AC	FY-30AC	FY-40AC	FY-50AC	FY-100AC	
4.4/38℃冷量 Cooking capacity(Kacl/h)		45000	54000	76600	92800	113000	243000	
压缩机 Compressor		全封闭涡旋式 All-closed Vorticity						螺杆压缩机 Screw compressor
压缩机输入功率 Compressor power(Kw)		18	20.4	26.8	35	40	74	
冷媒 Refrigerant		R22(R407,R502环保型选配)						
冻水泵输入功率 Chilled water pump power(Kw)		2.2	2.2	4	7.5	7.5	8	
10℃冷冻水最大流量 Max flow rate of chilled water(L/min)		400	400	400	600	600	900	
最大扬程 Max pressure(M)		30	30	50	55	55	60	
冻水进出水管 Flow water inlet and outlet pipe(″)		2″	2″	2″	3″	3″	5″	
冷却风机功率 Cooling fan power(Kw)		1	1.5	1.5	3.2	3.2	5	
风冷箱式外形	长 Size length(mm)	1800	1800	2300	2000	2100	3600	
	宽 Size width(mm)	1300	1300	1300	1200	1300	1800	
	高 Size height(mm)	1600	1600	1600	2100	2100	1800	
水箱容量 Water tank capa.(L)		351	351	468	无水箱(干式蒸发器) Non-water box(dry-type)			
重量 Weight(Kg)		700	750	820	980	1600	2800	