

规格 Specifications		FY-03WC	FY-05WC	FY-08WC	FY-10WC	FY-12WC	FY-15WC	
4.4/38℃冷量 Cooking capacity(Kacl/h)		7580	13500	21150	28000	34400	41000	
压缩机 Compressor		全封闭涡旋式 All-closed Vorticity						
压缩机输入功率 Compressor power(Kw)		2.5	4.4	7	9	10.2	13.4	
冷媒 Refrigerant		R22(R407,R502环保型选配)						
冻水泵输入功率 Chilled water pump power(Kw)		0.75	0.75	0.75	0.75	1.5	1.5	
10℃冷冻水最大流量 Max flow rate of chilled water(L/min)		55	120	120	200	400	400	
最大扬程 Max pressure(M)		9	9	9	16	20	20	
冻水进出水管 Flow water inlet and outlet pipe(°)		1°	1°	1°	1.5°	1.5°	1.5°	
冷却水流量 Condensing water rate(L/min)		≥36	≥60	≥100	≥135	≥200	≥200	
冷却水接管 Chiller water inlet and outlet pipe(°)		1°	1°	1.5°	1.5°	1.5°	1.5°	
水冷箱式外形	长 Size length(mm)	900	900	1400	1500	1500	1600	
	宽 Size width(mm)	600	600	750	750	750	900	
	高 Size height(mm)	1000	1000	1050	1050	1050	1050	
水箱容量 Water tank capa.(L)		40.5	40.5	117	160	160	234	
重量 Weight(Kg)		180	220	320	400	420	450	

规格 Specifications		FY-20WC	FY-25WC	FY-30WC	FY-40WC	FY-50WC	FY-100WC	
4.4/38℃冷量 Cooking capacity(Kacl/h)		50000	60000	77600	101780	121400	246000	
压缩机 Compressor		全封闭涡旋式 All-closed Vorticity						螺杆压缩机 Screw bar compressor
压缩机输入功率 Compressor power(Kw)		18	20.4	26.8	35	40	74	
冷媒 Refrigerant		R22(R407,R502环保型选配)						
冻水泵输入功率 Chilled water pump power(Kw)		2.2	2.2	4	7.5	7.5	8	
10℃冷冻水最大流量 Max flow rate of chilled water(L/min)		400	400	400	600	600	900	
最大扬程 Max pressure(M)		30	30	50	55	55	60	
冻水进出水管 Flow water inlet and outlet pipe(°)		2°	2°	2°	3°	3°	5°	
冷却水流量 Condensing water rate(L/min)		≥240	≥300	≥300	≥340	≥400	≥800	
冷却水接管 Chiller water inlet and outlet pipe(°)		2°	2°	2°	2°	2°	4°	
水冷箱式外形	长 Size length(mm)	1800	1800	2300	2100	2300	2500	
	宽 Size width(mm)	1300	1300	1300	1200	1400	1500	
	高 Size height(mm)	1050	1050	1100	1500	1500	1700	
水箱容量 Water tank capa.(L)		351	351	468	无水箱(干式蒸发器) Non-water box(dry-type)			
重量 Weight(Kg)		550	650	750	860	1200	2200	