

技术参数表			TECHNICAL DATA						YE150W		
规格	Specification		200VE/200V			300VE/300V			430VE/430V		
注射部件	Injection Unit	单位	A	B	C	A	B	C	A	B	C
螺杆直径	Screw diameter	[mm]	28	32	36	32	36	40	36	40	45
长径比	Screw L/D ratio	[L/D]	22	21	18.7	23.6	21	19	23.3	21	19
注射容积	Cylinder head volume	[cm³]	77	100	127	116	147	182	173	213	270
注射重量	Shot weight	[g]	70	91	116	106	134	166	157	194	246
注射压力	Injection pressure	[Mpa]	261	200	158	253	200	162	247	200	158
注射速率	Injection rate	[g/s]	112/196	146/256	185/324	146/256	185/324	229/400	185/324	229/400	290/507
注射速度	Shot speed	[mm/s]	200/350			200/350			200/350		
注射行程	Injection stroke	[mm]	125			145			170		
螺杆转速	Screw speed	[rpm]	400			400			400		
喷嘴接触力	Nozzle touch force	[KN]	19.7			19.7			19.7		
喷嘴球径	Sphere diameter of nozzle	[mm]	SR10			SR10			SR10		
合模装置	Clamping Unit										
合模力	Clamping force	[KN]	1500								
最大开模行程	Max.mould opening stroke	[mm]	420								
拉杆间距	Space between tie bars	[mm]	530 x 470								
最小模具尺寸	Min.Mould size	[mm]	335 x 305								
最小模厚	Min.Mould height	[mm]	200								
最大模厚	Max.Mould height	[mm]	520								
模厚定位孔直径	Dia of mould location hole	[mm]	Φ125H7								
顶出行程	Ejector stroke	[mm]	120								
顶出力	Ejector force	[KN]	32.4								
顶出杆数	Ejector number	[PIECE]	5								
其他	Others										
电机功率	Motor power	[Kw]	19.3/19.3			23.6/22			25.2/30		
料筒电热功率	Heating power	[Kw]	9.25			13			14.2		
加热段	Heating section		3+3			3+3			3+3		
机器尺寸	Machine dimension	[m]	5.47 x 1.7 x 1.84			5.48 x 1.7 x 1.84			5.68 x 1.7 x 1.84		
机器重量	Machine weight	[t]	6.3			6.5			6.8		

注意：*公司具有随时更改型号、参数、规格、配置、颜色的权力，恕不另行通知。
Attention: * Our company reserves the right of changing model, parameter, specification, configuration and color without prior notice.