

技术参数表			TECHNICAL DATA						YE190W		
规格	Specification		300VE/300V			430VE/430V			640VE/640V		
注射部件	Injection Unit	单位	A	B	C	A	B	C	A	B	C
螺杆直径	Screw diameter	[mm]	32	36	40	36	40	45	40	45	50
长径比	Screw L/D ratio	[L/D]	23.6	21	19	23.3	21	19	23.5	21	19
注射容积	Cylinder head volume	[cm³]	116	147	182	173	213	270	252	319	395
注射重量	Shot weight	[g]	106	134	166	157	194	246	229	290	358
注射压力	Injection pressure	[Mpa]	253	200	162	247	200	158	253	200	162
注射速率	Injection rate	[g/s]	146/256	185/324	229/400	185/324	229/400	290/507	183/343	231/434	286/536
注射速度	Shot speed	[mm/s]	200/350			200/350			160/300		
注射行程	Injection stroke	[mm]	145			170			200		
螺杆转速	Screw speed	[rpm]	400			400			350		
喷嘴接触力	Nozzle touch force	[KN]	19.7			19.7			39.3		
喷嘴球径	Sphere diameter of nozzle	[mm]	SR10			SR10			SR10		
合模装置	Clamping Unit										
合模力	Clamping force	[KN]	1900								
最大开模行程	Max.mould opening stroke	[mm]	470								
拉杆间距	Space between tie bars	[mm]	590 x 530								
最小模具尺寸	Min.Mould size	[mm]	355 x 335								
最小模厚	Min.Mould height	[mm]	200								
最大模厚	Max.Mould height	[mm]	550								
模厚定位孔直径	Dia of mould location hole	[mm]	Φ160H7								
顶出行程	Ejector stroke	[mm]	130								
顶出力	Ejector force	[KN]	44.1								
顶出杆数	Ejector number	[PIECE]	5								
其他	Others										
电机功率	Motor power	[Kw]	23.6/23.4			27.9/30			29/30		
料筒电热功率	Heating power	[Kw]	13			14.2			16.6		
加热段	Heating section		3+3			3+3			3+3		
机器尺寸	Machine dimension	[m]	6.0 x 1.68 x 1.92			6.0 x 1.68 x 1.92			6.25 x 1.68 x 1.92		
机器重量	Machine weight	[t]	8.1			8.2			8.6		

注意：*公司具有随时更改型号、参数、规格、配置、颜色的权力，恕不另行通知。

Attention: * Our company reserves the right of changing model, parameter, specification, configuration and color without prior notice.