

规格参数 Main Specification											
机型MODEL	单位UNIT	FG700-ID5	FG700-WD5	FG800-WD5	FG900-WD5	FG1100-WD5	FG1300-WD5	FK1100-WD5	FK1300-WD5	FK1500-WD5	FK1700-WD5
适用成型机(TON) I.M.M.range	Ton	80-200	80-200	150-280	200-350	250-480	380-600	250-480	450-600	850-1300	850-1600
手臂形式 Type	mm	单段 Single-Stage	双段(倍速式)(Telescopic type)								
上下行程(Y轴) Vertical stroke	mm	P:700 R:700	P:700 R:700	P:800 R:800	P:900 R:900	P:1100 R:1100	P:1300 R:1300	P:1100 R:1100	P:1300 R:1300	P:1500 R:1500	P:1700 R:1700
引拔行程(X轴) Crosswise stroke	mm	P:100~600 R:100~450	P:120~600 R:120~450	P:140~700 R:120~540	P:140~800 R:120~640	P:220~950 R:150~730	P:220~1050 R:150~830	P:220~950 R:150~730	P:250~1050 R:200~800	P:300~1200 R:250~900	P:300~1300 R:250~1000
横出行程(Z轴) Swing Stroke	mm	1200	1400	1400	1600	1850	2050	1850	2050	2300	2500
最大荷重 MAX load	kg	5	5	5	5	10	10	10	10	20	20
最小取出时间 Minimum take time	sec	1.3	1.2	1.5	1.5	2	2	2	2	3.5	3.8
空循环时间(不含治具) Dry cycle time(without tool)	sec	5.5	5.5	5.8	6	6.5	6.7	6.5	6.5	7.5	8
驱动方式 Drive System	-	X、Z、Y-伺服马达(X、Z、Y-servo motor)									
工作气压 Working Air pressure	Kgf/cm <sup>2</sup>	5~7									
空气消耗量 Air Consumption	nl/cycle	20	20	20	20	20	20	20	20	40	45
电源消耗量 Power Consumption	KVA	5.2	5.2	6	6	8.2	8.2	8.2	8.2	10.8	10.8
电源 Power	-	AC220V+10% 50/60HZ					AC380V+10% 50/60HZ				
净重 Net Weight	kg	230	300	320	350	500	520	520	540	1130	1150